Innovative High Power LED Flood Light





Model LD-FL-200W-CL7

Specification

Light Source: LED

Input Voltage(V): 85-265V

Lamp Luminous Efficiency(Im/w): 85

Beam Angle(*): 120

Lamp Body Material: Aluminum

Place of Origin: Guangdong, China

(Mainland)

Weight: 14 kg

Power Factor: >0.95

Cover Material: Tempered glass

Item Type: Flood Lights

Lamp Power(W): 200

CRI (Ra>): 80

Working Temperature(°C): -20 - 60

IP Rating: IP65

Brand Name: LEAD

Input Voltage: 85-265V Higher voltage

available

Frequency: 47-63HZ

Application: Billboard, Plaza, park, industrial building, Gym, gas station etc. LED Light Source: Epistar/Bridgelux

Lamp Luminous Flux(Im): 17000LM

Color Temperature(CCT): Pure White

Working Lifetime(Hour): 50000

Certification: CE,EMC,LVD,RoHS,SAA

Model Number: LD-FL-200W-CL7

Fixture Color: Black

Beam Angel: 120degree

Waterproof Rating: IP65

Delivery Time: 5-7 days

Features:

Die casting aluminum housing and high intensity toughened glass cover

Finished with epoxy powder paint, resistant to corrosion

Finished regular colour:Black

High quality anodised aluminium reflector

High efficiency and power factor Meanwell LED driver

Stainless steel screw

Water-proof and durable silicon rubber sealing gasket

Instant start, flicker free, energy saving

Episatr/Bridgelux high bright LED COB and ideal heat dissipation design



Room B3, 18/F Bonsun Industrial Building, 364-366 Sha Tsui Road, Tsuen Wan.

Phone: 852-35863418 Fax: 852-23212617 info@ilighting.com.hk